

BOX N135 R

CONCRETE MIXER

Applications: Easy assembly/disassembly and low noise levels make it particularly suitable for indoor work.

Electric safety

Fitted with double insulation, the Box N 135 R concrete mixer is designed to the EN 12151 standard and protected against water splashes (IP 55) as well as against overloading and accidental restarting following a lack of voltage.

Motor reducer details: Motor reducer with reducer in pressure die-cast aluminium with gears in oil-bath protected by high-resistance, shockproof plastic shell



CHARACTERISTICS

- Single phase motor 230V/50 Hz
- Entirely built in steel
- Switch with IP 55 minimum voltage coil and plug
- Electric safety: designed to the EN 12151 standard, double insulation, protection against water splashes (IP 55), as well as overloading and accidental restarting following a lack of voltage.
- Locking system to prevent tipping during transport
- Steel mixing blades
- Semi pneumatic rubber wheels
- Cardboard packing

TECHNICAL DATA

N 135R

| | | |
|----------------------|----|-------|
| Drum capacity | lt | 140 |
| Output | lt | 100 |
| Mixes per hour | n. | 26 |
| Electric motor power | Kw | 0,3 |
| Weight | kg | 55 |
| Length | cm | 107 |
| Width | cm | 71 |
| Height | cm | 140 |
| Value Lpa g | dB | 70 |
| Value Lpc peak g | dB | < 130 |

*Output varies according to type of material

Quick and easy assembly

Assembling and disassembling the Box N 135 R are easy operations requiring 3 minutes. After use this unit can be disassembled into its three main parts or placed in its box. Professional and easy to handle, this concrete mixer runs quietly and is therefore is the ideal solution for work on building sites where the norms concerning noise levels have to be respected

Disassembled machine delivered in a box
Dim. 66 x 66 x 66 cm



Edil Lame srl
Macchine Edil | Poggibonsi | Italia
edillame.com

MADE IN ITALY